

Plastic Surface Treating for the 21st Century

LT 2000

Consistent 3-D Surface Treatment of Your Plastic Parts

3-D Open Atmospheric Plasma Plastic Surface Treating Systems



LECTRO-TREAT

Lectro Engineering Co.
1643 Lotsie Blvd
St. Louis, MO 63132
USA

Since 1960

www.lectrotreat.com
Email: lectro@lectrotreat.com
Phone: 314-567-3100
Fax: 314-567-3466

Markets That Utilize The Lectro Treat System

Automotive

Promotional

Containers

Medical

Recreational

Electronic

Industrial

Features

Benefits

Surface Treatment Levels >70 dynes/cm ² over the entire outside of three dimensional plastic parts.	Allows the decoration/adhesion on plastic parts without the use of costly primers or chemical wipes.
Open Atmosphere Plasma	Continual process, no vacuum required, higher production rates.
Versatility	No set-up required for different shapes resulting in labor and production savings.
No Heat	Zero scrap due to heat warping, surface crazing, stress relieving and paneling. Maintains the surface integrity of your plastic parts. Thin walling of parts made possible resulting in material saving.
Safe Equipment	Lower insurance premiums, no open flames.
Efficient Operation	Low cost power consumption.
Low Frequency 50-60HZ	No interference with Electronic/PLC/Computers controls.
Low Maintenance	Only periodic cleaning necessary.
PLC Controls	Reliable and repeatable production rates, allows interface with entire production line.
Cold Plasma	360 degree uniform surface treatment guaranteed.

Specifications

Input Voltage	Standard 240 volt, 3 phase Any voltage can be accommodated
Frequency	50-60HZ
Total Electrical Load	5 KVA on standard units
Certification	UL, CSA or CE components
Equipment Dimensions	38" wide x 72" long x 60" height 12" conveyor extension each end
Conveyor Height	37" above the floor
Complete System	Standard unit includes surface treating, conveyor and exhaust systems.
Custom Design	Available upon request

Video and CD available to show application and operation